



淡陶社  
DANTO-SHA

AWAJI

8"

1 3/4" X 9 1/2"

According to Japanese mythology, Awaji Island is believed to be the first island created by the two deities who gave birth to the land of Japan. Named AWAJI in honor of its birthplace, this collection is offered in four colors inspired by the island's native materials - salt, sand, and clay of remarkable quality:

- WHITE — Tan-en Evoking the refined whiteness of Awaji's high-quality sea salt.
- BLACK — Gen-tan Inspired by the deep tones of traditional Awaji roof tiles.
- BROWN — Tan-do Drawn from the rich brown clay found in western Awaji.
- BEIGE — Suna Inspired by the natural sea sand of eastern Awaji.



This is AWAJI. A collaboration shaped by place, history, and enduring craft.

<https://cepactile.com/product/awaji-8/>

<https://cepactile.com/product/awaji-border/>

## RECOMMENDED AREAS OF USE

With regard to the durability of the bisque and glaze, this material is suitable for:

- All countertop applications - residential and commercial
- Fireplace surround, hearth and firebox
- Commercial and residential flooring applications
- All interior and exterior wall applications - residential and commercial including building facades, swimming pools, fountains, outdoor kitchens and regions that experience extreme weather conditions subject to the method of installation

## INSTALLATION METHOD

- Please refer to the TCNA handbook for installation method: <http://www.tcnatile.com/>
- Always inspect material prior to installation, for color, shade, size, mounting and any other deciding factors as installed material cannot be accepted for return or credit. Use signifies acceptance.
- Recommended Grout Joint Minimum 3/16" for both sizes.
- Awaji is easily maintained due to the application of a sealer prior to the firing process. In this regard, sealing is not necessary prior to grouting or after installation.
- Material can be cleaned with any mild nonabrasive household cleaning product due to the chemical resistant nature of the glaze.

## TECHNICAL DATA

- Japanese Porcelain – fired at approx. 2300° Fahrenheit
- Chemical Resistant
- Frost Proof – *subject to method of installation*
- VOC Free
- Water absorbency
  - Bisque less than 1%
  - Glazed surface 0%
- TCNA – MOH's Scale Rating 7
- TCNA – DCOF rating pending - should meet 0.42

8":

- Loose pieces: 3 pcs. = 1.3 sq. ft. / 13 sq. ft. per box
- Weight: 4.85 lbs. per sheet / 49 lbs. per box
- Thickness: 5/16"

1 3/4" x 9 1/2":

- Loose pieces: 9 pcs. = 1 sq. ft. / 8 sq. ft. per box
- Weight: 3.95 lbs. per 9 pcs. / 32 lbs. per box
- Thickness: 5/16"

- Pre-consumer recycled content – 30%

Variations of shade are inherent characteristics of all kiln fired products. To ensure satisfaction, please visually inspect all merchandise prior to installation, as use signifies acceptance.

We will endeavor to resolve any issues that may arise with material purchased prior to installation.

747-224-0600 | [www.cepactile.com](http://www.cepactile.com) | [customercare@cepactile.com](mailto:customercare@cepactile.com)