



FLORA

https://cepactile.com/product/flora/

PROFILE

Note:

- Minimum order quantity is one box.
- Full box quantities only.
- General lead time approx. 45 90 days.
- Random blends can be created by using up to three colors.
- Personalized designs and patterns are also available on a custom order basis. Please contact your Cepac Representative for additional information and pricing.
- Due to the handmade and hand painted nature of the Flower deco, there is a wide variation in the glazing and texture from piece to piece and each production run.



747-224-0600 www.cepactile.com customercare@cepactile.com

Where Excellence in Quality & Service Unite!

RECOMMENDED AREAS OF USE

With regard to the durability of the bisque and glaze, this material is suitable for:

- All vertical applications residential and commercial
- All interior wall and countertop
- Fireplace surround, hearth and firebox
- Light commercial flooring applications with the exception of the Flower deco
- All exterior wall applications including building facades, swimming pools, fountains and outdoor kitchens, including regions that experience extreme weather conditions, subject to the method of installation

INSTALLATION AND MAINTENANCE

- Please refer to the TCNA handbook for installation method <u>http://www.tcnatile.com/</u>
- Always inspect material prior to installation, for color, shade, size, mounting and any other deciding factors as installed material cannot be accepted for return or credit. Use signifies acceptance.
- Please note that mesh mounted goods should never be placed directly on the wet saw for cutting. If cuts are required, pieces should be removed from the mesh and cut individually to avoid the glue releasing from the mesh.
- Material can be cleaned with any mild nonabrasive household cleaning product due to the chemical resistant nature of the glaze.

TECHNICAL DATA

- Japanese Porcelain fired at approx. 2300 degrees Fahrenheit
- Chemical Resistant
- Frost Proof subject to method of installation
 - Water absorbency
 - Bisque less than 1%
 - Glazed surface 0%
 - TCNA MOH's Scale Rating 7
- TCNA DCOF: Does not meet a 0.42 rating
- Mesh mounted 1 sheet = 0.76 sq. ft. / 15.2 sq. ft. per box
- Sheet size: nominal 11" x 11"
- Weight: 2 lbs. per sq. ft. / 40 lbs. per box
- Thickness: 1/4"

•

- Pre-consumer recycled content 21%
- Variations of shade are inherent characteristics of all kiln fired products. To ensure satisfaction, please visually inspect all merchandise prior to installation, as use signifies acceptance.
- We will endeavor to resolve any issues that may arise with material purchased prior to installation.