



## RECOMMENDED AREAS OF USE

With regard to the durability of the bisque and glaze, this material is suitable for:

- All vertical applications - residential and commercial
- All interior walls
- Fireplace surround and firebox
- All exterior wall applications including building facades, swimming pools, fountains and outdoor kitchens, including regions that experience extreme weather conditions, subject to the method of installation



## FRAME

4" x 12"

<https://cepactile.com/product/frame/>

### PROFILE

747-224-0600

[www.cepactile.com](http://www.cepactile.com)

[customercare@cepactile.com](mailto:customercare@cepactile.com)

*Where Excellence in Quality & Service Unite!*

## INSTALLATION AND MAINTENANCE

- Please refer to the TCNA handbook for installation method <http://www.tcnatile.com/>
- Always inspect material prior to installation, for color, shade, size, mounting and any other deciding factors as installed material cannot be accepted for return or credit. Use signifies acceptance.
- Recommended Grout Joint: 3/16" or greater
- Material can be cleaned with any mild nonabrasive household cleaning product due to the chemical resistant nature of the glaze.

## TECHNICAL DATA

- Japanese Porcelain – fired at approx. 2300 degrees Fahrenheit
- Chemical Resistant
- Frost Proof – subject to method of installation
- Water absorbency
  - Bisque less than 1%
  - Glazed surface 0%
- TCNA – MOH's Scale Rating 7
- TCNA – DCOF Average rating not applicable
- Loose pcs. – 3 pcs. = 0.93 sq. ft. / 27 pcs. = 8.37 sq. ft. per box
- Weight – 5.15 lbs. per sq. ft. / 48 lbs. per box
- Thickness – 1/2"
- Pre-consumer recycled content – 53.6%
- Variations of shade are inherent characteristics of all kiln fired products. To ensure satisfaction, please visually inspect all merchandise prior to installation, as use signifies acceptance.
- We will endeavor to resolve any issues that may arise with material purchased prior to installation.