



KB BORDER

3/4" x 5-3/8"
Straight Joint
Stagger Joint

<https://cepactile.com/product/kb-border/>

PROFILE

Note:

- Minimum order quantity is one box.
- Full box quantities only.
- General lead time approx. 45 to 90 days.
- Random blends can be created by using up to three colors.
- KB-M-77 with crackled glaze should be sealed with a penetrating sealer prior to grouting

747-224-0600

www.cepactile.com

customercare@cepactile.com

Where Excellence in Quality & Service Unite!

RECOMMENDED AREAS OF USE

With regard to the durability of the bisque and glaze, this material is suitable for:

- All vertical applications - residential and commercial
- All interior wall and countertop
- Fireplace surround, hearth and firebox
- Light commercial flooring applications
- All exterior wall applications including building facades, swimming pools, fountains and outdoor kitchens, including regions that experience extreme weather conditions, subject to the method of installation

INSTALLATION AND MAINTENANCE

- Please refer to the TCNA handbook for installation method <http://www.tcnatile.com/>
- Always inspect material prior to installation, for color, shade, size, mounting and any other deciding factors as installed material cannot be accepted for return or credit. Use signifies acceptance.
- Please note that mesh/paper face mounted goods should never be placed directly on the wet saw for cutting. If cuts are required, pieces should be removed from the mesh/paper and cut individually to avoid the glue releasing from the mesh/paper.
- Material can be cleaned with any mild nonabrasive household cleaning product due to the chemical resistant nature of the glaze.

TECHNICAL DATA

- Japanese Stoneware
- Chemical Resistant
- Frost Proof – subject to method of installation
- Water absorbency
 - Bisque less than 1%
 - Glazed surface 0%
- TCNA – MOH's – Not available
- TCNA – DCOF – Does not meet a 0.42 rating
- Straight Joint:
 - 1 sheet = 0.97 sq. ft. / 19.4 sq. ft. per box
 - Sheet size: nominal 11.50" x 11.50"
 - Weight: 2.45 lbs. per sq. ft. / 50 lbs. per box
- Stagger Joint:
 - 1 sheet = 0.97 sq. ft. / 19.4 sq. ft. per box
 - Sheet size: 14.50" x 11.50"
 - Weight: 2.45 lbs. per sq. ft. / 50 lbs. per box
- Paper face mounted only
- Thickness: 5/16"
- Pre-consumer recycled content – 48.5%
- Variations of shade are inherent characteristics of all kiln fired products. To ensure satisfaction, please visually inspect all merchandise prior to installation, as use signifies acceptance.
- We will endeavor to resolve any issues that may arise with material purchased prior to installation.