



Where Excellence in Quality & Service Unite!

<https://cepactile.com/product/kanjaku-16/>

<https://cepactile.com/product/kanjaku-46/>

Kanjaku, meaning calm and serene in Japanese, reflects a philosophy of quiet beauty. The glazes in this collection are designed to evoke tranquility, balance and a timeless sense of peace. The series is offered in two formats - a 1" x 6" stacked mesh mounted mosaic and a 4" x 6" loose piece offering, available in four thoughtfully curated glazes.

Coordinating Trim: Jolly Piece 9/16" x 6" Bead

Please note the Jolly pieces are coordinating trims that are fired at different times than the field tile. In this regard, there can be wide shade variations between the field and trim pieces.



KANJAKU

1" X 6"

4" X 6"

RECOMMENDED AREAS OF USE

With regard to the durability of the bisque and glaze, this material is suitable for:

- All countertop applications - residential and commercial
- Fireplace surround, hearth and firebox
- Light commercial flooring applications and residential flooring applications
- All interior and exterior wall applications - residential and commercial including building facades, swimming pools, fountains, outdoor kitchens and regions that experience extreme weather conditions subject to the method of installation

INSTALLATION METHOD

- Please refer to the TCNA handbook for installation method: <http://www.tcnatile.com/>
- Always inspect material prior to installation, for color, shade, size, mounting and any other deciding factors as installed material cannot be accepted for return or credit. Use signifies acceptance.
- Recommended Grout Joint 4"x6": Minimum 1/8"
- Material can be cleaned with any mild nonabrasive household cleaning product due to the chemical resistant nature of the glaze.

TECHNICAL DATA

- Japanese Porcelain – fired at approx. 2300° Fahrenheit
 - Chemical Resistant
 - Frost Proof – *subject to method of installation*
 - VOC Free
 - Water absorbency
 - Bisque less than 1%
 - Glazed surface 0%
 - TCNA – MOH’s Scale Rating 7
 - TCNA – DCOF – Does not meet a 0.42 rating
- 1" x 6":**
 - Mesh mounted: 1 sheet = 0.97 sq. ft. / 19.4 sq. ft. per box
 - Sheet size: nominal 11.75" x 11.75"
 - Weight: 3.1 lbs. per sheet / 62.6 lbs. per box
 - Thickness: 5/16"
 - 4" x 6":**
 - Loose pieces: 8 pcs. = 1.2 sq. ft. / 12 sq. ft. per box
 - Weight: 4.2 lbs. per 8 pcs. / 42.65 lbs. per box
 - Thickness: 1/4"
 - Pre-consumer recycled content – 33%

Variations of shade are inherent characteristics of all kiln fired products. To ensure satisfaction, please visually inspect all merchandise prior to installation, as use signifies acceptance.

We will endeavor to resolve any issues that may arise with material purchased prior to installation.