



Where Excellence in Quality & Service Unite!

## CEPAC CUSTOM ORDER PROGRAM

<https://cepactile.com/product/tsudumi-custom-order/>

Borrowing its shape from the two-headed traditional Japanese drum of a similar name, Tsudumi is a refreshingly unconventional mosaic tile with loads of personality.

Minimum order quantity is one box. | Full box quantities only.

General lead time is approx. 45 to 90 days.

Random Blends can be created by using up to three colors.

Please contact your Cepac representative for additional information and pricing.

# TSUDUMI

1 1/2"



## RECOMMENDED AREAS OF USE

With regard to the durability of the bisque and glaze, this material is suitable for:

- All countertop applications - residential and commercial
- Fireplace surround, hearth and firebox
- Light commercial flooring applications and all residential applications
- All interior wall applications - residential and commercial
- All exterior wall applications - residential and commercial including building facades, swimming pools, fountains, outdoor kitchens and regions that experience extreme weather conditions, subject to the method of installation

## INSTALLATION METHOD

- Please refer to the TCNA handbook for installation method: <http://www.tcnatile.com/>
- Always inspect material prior to installation, for color, shade, size, mounting and any other deciding factors as installed material cannot be accepted for return or credit. Use signifies acceptance.
- Please note that mesh mounted goods should never be placed directly on the wet saw for cutting. If cuts are required, pieces should be removed from the mesh and cut individually to avoid the glue releasing from the mesh.
- Material can be cleaned with any mild nonabrasive household cleaning product due to the chemical resistant nature of the glaze.

## TECHNICAL DATA

- |  |   |
|--|---|
| • Japanese Porcelain – fired at approx. 2300° Fahrenheit | • TCNA – MOH's Scale Rating 7                                 |
| • Chemical Resistant                                     | • TCNA – DCOF: Does not meet a 0.42 rating                    |
| • Frost Proof – <i>subject to method of installation</i> | • Mesh mounted: 1 sheet = 0.95 sq. ft. / 20.9 sq. ft. per box |
| • Water absorbency                                       | • Sheet size: nominal 11.75" x 11.75"                         |
| ◦ Bisque less than 1%                                    | • Weight: 1.85 lbs. per sheet / 41 lbs. per box               |
| ◦ Glazed surface 0%                                      | • Thickness: 1/4"   |
|  | • Pre-consumer recycled content – 21%                         |

Variations of shade are inherent characteristics of all kiln fired products. To ensure satisfaction, please visually inspect all merchandise prior to installation, as use signifies acceptance.

We will endeavor to resolve any issues that may arise with material purchased prior to installation.

747-224-0600 | [www.cepactile.com](http://www.cepactile.com) | [customercare@cepactile.com](mailto:customercare@cepactile.com)