



RECOMMENDED AREAS OF USE

With regard to the durability of the bisque and glaze, this material is suitable for:

- All vertical applications - residential and commercial
- All interior walls
- Fireplace surround and firebox
- All exterior wall applications including building facades, swimming pools, fountains and outdoor kitchens, including regions that experience extreme weather conditions, subject to the method of installation



VERDON

2 ½" x 9"
Concaved Hexagon

<https://cepactile.com/product/verdon/>

PROFILE

747-224-0600

www.cepactile.com

customercare@cepactile.com

Where Excellence in Quality & Service Unite!

INSTALLATION AND MAINTENANCE

- Please refer to the TCNA handbook for installation method <http://www.tcnatile.com/>
- Always inspect material prior to installation, for color, shade, size, mounting and any other deciding factors as installed material cannot be accepted for return or credit. Use signifies acceptance.
- Recommended Grout Joint: 1/8" or greater
- Material can be cleaned with any mild nonabrasive household cleaning product due to the chemical resistant nature of the glaze.

TECHNICAL DATA

- Japanese Porcelain – fired at approx. 2300 degrees Fahrenheit
- Chemical Resistant
- Frost Proof – subject to method of installation
- Water absorbency
 - Bisque less than 1%
 - Glazed surface 0%
- TCNA – MOH's Scale Rating 7
- TCNA – DCOF Average rating not applicable
- Loose pieces – 10 pieces = 1 sq. ft. / 50 pieces = 5 sq. ft. per box
- Weight – 4.05 lbs. per sq. ft. / 21 lbs. per box
- Thickness – 3/8"
- Pre-consumer recycled content – 52%
- Variations of shade are inherent characteristics of all kiln fired products. To ensure satisfaction, please visually inspect all merchandise prior to installation, as use signifies acceptance.
- We will endeavor to resolve any issues that may arise with material purchased prior to installation.